

CHAINSTITCH SEWING MACHINE



KX-101 Blind Stitch Machine



- KX 101 is basic hemming machine. it is Widely used for hemming cuff, pant, shirt, glove, sock, front and back of western suit, etc and can stitch various material such as cotton, wool, chemical fiber, etc.



MACHINE	NEEDLE	STITCH LENGTH (mm)	MOTOR SPEED (w)	GW/NW (kg)	PACKING SIZE (mm)
KX-101	LWX6T #11~#14	3 ~ 8	250	25/20	350 X 250 X 325

KX-2000 C Two Needle Belt Loop Machine



- This bottom coverstitcher is equipped with a front cutter to trim the extra edge of fabrics to the proper width for making belt loops.
- This machine is applicable for denim and cotton materials.



MACHINE	NEEDLE	NO.OF NEEDLE	THREADS	GAUGE (mm)	PRESSER FOOT LIFT (mm)	STITCH LENGTH (mm)	MOTOR SPEED (RPM)	MOTOR (w)	Gw/Nw (kg)	PACKING SIZE (mm)
KX-2000 C	TV X 5 #18~#21	2	3	6.4	10	8~16	4000	400	48/44	635 X 450 X 650
KX-2000 C P (With Puller)	TV X 5 #18~#21	2	3	6.4	10	8~16	4000	400	48/44	635 X 450 X 650

CHAINSTITCH SEWING MACHINE



GK-68 Pin Point Stitch Machine / Saddle Stitch Machine



- Simple and resonable structure. It adopts looper type mechanism. Heavy and light thread can easily pass through the Looper and Needle.
- Gear driven, auto lubrication, stable operation, low noise, endurable, easy for operation and repair.
- Adopt sperical crankshaft driven to ensure stable and beautiful stitch, good for various thin and heavy materials.
- This machine is applicable for suits, coats, shirts, etc.

Looper System For Heavy Material



MACHINE	NEEDLE	STITCH LENGTH (mm)	PRESSURE FOOT LIFT (mm)	MOTOR SPEED (RPM)	PACKING SIZE (mm)
GK 68	SCHMETZ 29C150#11-#18	3~5	5	2000	600 X 230 X 560

KX-928KH2PL / XHPS / XHPL Feed Of The Arm Machine For Heavy Material



- The special structure of cantilever tubular is suitable for sleeves, trousers and simlier kind of joint sewing.
- Exteriorly equipped with up-down puller system, suitable for thick materials.
- It is suitable for Men's Suit, suit-Dress, Work Suits, Jeans, Tent etc.,



MACHINE	NEEDLE	NO.OF NEEDLE	GAUGE (mm)	PRESSURE FOOT LIFT (mm)	STITCH LENGTH (mm)	MOTOR SPEED (RPM)	MOTOR (w)	PACKING SIZE (mm)
KX-928 XH PL	TVX5 #18~#21	3	6.4 (1/4)	12	3.0 ~ 4.5	3600	400	580 X 480 X 530
KX-928-XH-2PL	TVX5 #18~#21	3	6.4 (1/4)	12	3.0 ~ 4.5	3600	400	580 X 480 X 530
KX-928-XH-PS	TVX5 #18~#21	3	6.4 (1/4)	12	3.0 ~ 4.5	3600	400	580 X 480 X 530